

FILE: 2021-D01VUL0

3.5X(N-1)+4.3

0.80

9.20

2.15

3.50X(N-1)

3.50

0.3

7.00

3.50±.30

3.00

PCB Layout

Total Pitch Tolerances

Nominal dimension range

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

REV EC.N NO.

CONTENT

CHK

DATE

NOTES:

UL Standard

1

Use group	B	C	D
Rated Current	8A	—	8A
Rated Voltage	300V	—	300V

IEC Standard

1

Pollution Degree	2
Overvoltage Category	I
Rate Impulse Voltage(kV)	2.5kV
Rate Voltage(V)	250V
Rate Current(A)	7A

NOTES2:

1.Housing: PA66(UL94V-0)

2.Solder Pin: Red copper(Sn Plated)

NOTES3:

1.Pitch: 3.5mm Poles: 02~24P

2.Operating temperature: -40℃~+105℃

3.RoHS Compliance

How to order

UL0-TB01 - 15VC/35 - XXP - Y 0 0 0 A

Certificate Factory poles
Series NO. Code

Customer requirements

color:

- 1:Grey
- 2:Blue
- 3:Black
- 4:Green
- 5:Orange
- 6:Red
- 7:transparent
- 8:Yellow
- 9:White

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
------	--------------	-------------	------	----------	------

DWG	LZW	DATE	21.05.27	UNITS	MM	SHEET/OF	1/1
-----	-----	------	----------	-------	----	----------	-----

CHK		DATE		SCALE	1:1	A4	
-----	--	------	--	-------	-----	----	--

APP		DATE		NAME	UL0-TB01-15VC/35-XXP-Y000A		
-----	--	------	--	------	----------------------------	--	--



NINGBO UL0 ELECTRONICS CO.,LTD.

宁波欧路电子有限公司

UL0TB0Y000A