

FILE: 2020-D01VUL0

REV	E.C.N NO.	CONTENT	CHK	DATE

NOTES1:

UL Standard

1.

Use group	B	C	D
Rated Current	8A	—	8A
Rated Voltage	300V	—	300V

3 Wire range:28-16AWG

IEC Standard

1.

Pollution Degree	2
Overvoltage Category	II
Rate Impulse Voltage(KV)	2.5KV
Rate Voltage(V)	250V
Rate Current(A)	7A

2.Torque value:M2.0.2Nm

3.Wire range:0.5-1.5mm²

NOTES2:

1.Housing: PA66(UL94.V-0)

2.Cover:PA66(UL94.V-0)

3.Cage:Brass(INi Plated)

4.Clamp:Phosphor Brons(INi Plated)

5.Screw:Steel(Zn Plated/M2.0)

6.Screw:Steel(Zn Plated/M2.5)

NOTES3:

1.Pitch: 3.50mm Poles: 02-24P

2.Stripping length: 7mm

3.Operating temperature: -40℃~+105℃

4.ReHS Compliance

How to order

UL0-TB13 - 15KM/3.81 - XXP - Y 0 0 0 A

Certificate Factory poles Customer requirements
Series NO. Code

color:

1:Grey 2:Blue 3:Black
4:Green 5:Orange 6:Red
7:transparent 8:Yellow 9:white

Total Pitch Tolerances

Nominal dimension range

—

—

//

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	LZW	DATE	21.04.28	UNITS	MM
CHK.	DATE	SCALE	1:1	SHEET/OF	1/1
APP.	DATE	NAME	UL0-TB13-15KM/3.81-XXP-Y000A		

NINGBO UL0 ELECTRONICS CO.,LTD.

DWGNO.

UL0TB13Y000A