

FILE: 2021-D01VUL0

REV

ECN NO.

CONTENT

CHK

DATE

NOTES:

UL Standard

1

Use group	B	C	D
Rated Current	10A	-	10A
Rated Voltage	300V	-	300V

2. Wire range: 22~14AWG

IEC Standard

1

Pollution Degree	2
Overvoltage Category	II
Rated Impulse Voltage(kV)	6kV
Rated Voltage(V)	450V
Rated Current(A)	24A

2. wire range: 1.0-2.5mm²

NOTES2:

- 1.Housing: PA66(UL94V-0)
- 2.Solder Pin: Brass(Tin Plated)
- 3.Screw: Steel(Zn Plated)
- 4.Spring: Stainless Steel

NOTES3:

- 1.Pitch: 7.5mm Poles: 02-24P
- 2.Stripping length: 6mm
- 3.Operating temperature: -40℃~+105℃
- 4.RoHS Compliance

How to order

UL0-IB37 - 300/7.5 - XXP - Y 0 0 0 A

Certificate Factory poles
Series NO. Code

Customer requirements

color:

- 1:Grey
- 2:Blue
- 3:Black
- 4:Green
- 5:Orange
- 6:Red
- 7:transparent
- 8:Yellow
- 9:White

Total Pitch Tolerances		Nominal dimension range		T		≡		—		//	
in mm		in mm									
over	over	over	over	over	over	over	over	over	over	over	over
0	30	53	70	90	115	150	200	250	0	30	53
to	to	to	to	to	to	to	to	to	to	to	to
30	53	70	90	115	150	200	250	320	30	53	70
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30
±0.35	±0.44	±0.55	±0.70	±0.75	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3
0.5											

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	LZW	DATE	21.05.27	UNITS	MM
CHK	DATE	SCALE	1:1	A4	1/1
APP.	DATE	NAME	UL0-IB37-300/7.5-XXP-Y000A		
		DWGNO.	UL0IB37Y000A		



NINGBO UL0 ELECTRONICS CO., LTD.
宁波欧路电子有限公司

