

		2		1	
REV	E.C.N. NO.	CONTENT	CHK	DATE	

NOTES:

UL Standard

1.

Use group	B	C	D
Rated Current	20A	—	10A
Rated Voltage	300V	—	300V

2. Wire range: 26~12AWG

3.Torque value: M2.5, 3.54Lb.in

IEC Standard

Pollution Degree	2
Overvoltage Category	II
Rate Impulse Voltage(KV)	4KV
Rate Voltage(V)	250V
Rate Current(A)	20A

2. Wire range: 0.5 ~ 2.5mm²

3. Torque value: M2.5, 0.4Nm

NOTES:

1.Housing(2P): PA66(UL94V-0)

2.Housing(3P): PA66(UL94V-0)

3. Solder Pin: Brass (Tin Plated)

4. Block: Brass (Ni Plated)

5.Screw: Steel(M2.5,Zn Plated)

NOTES:

1.Pitch: 5.0mm Poles: 02-24P

2.Stripping Length: 8mm

32. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4. RoHS Compliance

How to order

JL0-TB25 - 129/5.0 - XXP - Y 00 0A

Certificate Series NO.	Factory Code	poles

Customer requirements

color: _____

- 1:Grey 6:Red
2:Blue 7:transparent
3:Black 8:Yellow
4:Green 9:white
5:Orange

ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE
------	--------------	-------------	------	----------	------

DWG.	LZW	DATE	21.05.08	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	1 : 1	A4	

APP.	DATE

 NINGBO ULO ELECTRONICS CO., LTD.	NAME
	ULO-TB25-129V5.0-XXP-Y000A



NINGBO ULO ELECTRONICS CO.,LTD.
宁波欧路电子有限公司

DWGNO. UL0TB25Y000A

NINGBO ULO ELECTRONICS CO.,LTD.

REV:1.0

L

1000