

		2		1	
REV	ECN NO.	CONTENT	CHK	DATE	

NOTES:

UL Standard

Use group	B	C	D
Rated Current	15A	—	10A
Rated Voltage	300V	—	300V

IEC Standard

Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	4.0KV
Rate Voltage(V)	320V
Rate Current(A)	20A

NOTES:

- 1.Housing: PA66(UL94V-0)
- 2.Solder Pin: Brass(Sn Plated)

NOTES:

- 1.Pitch: 3.5mm Poles:02-24P
2.Operating temperature: -40℃~+105℃
3.RoHS Compliance






How to order

UL0-TB01	-	15A/3.5	-	XXP	-	Y	0 0 0A
----------	---	---------	---	-----	---	---	--------

Certificate Series NO.	Factory Code	poles	Customer requirements
---------------------------	-----------------	-------	--------------------------

color:

- 1:Grey 6:Red
2:Blue 7:transparent
3:Black 8:Yellow
4:Green 9:White
5:Orange

[illegible]

ITEM	NAME OF PART	NO. OF PART	Q-TY	MATERIAL	NOTE	
DWG.	LZW	DATE 2021.03.26	UNITS	MM	SHEET/OF	1/1
G/K.	DATE		SCALE	1:1	A4	
APP.	DATE					



NINGBO UL0 ELECTRONICS CO., LTD
宁波欧路电子有限公司

DWGNO.	ULOTB01Y000A
--------	--------------