

		2		1	
REV	E.C.N NO.	CONTENT	CHK	DATE	

NOTES:

UL Standard

1.

Use group	B	C	D
Rated Current	8A	—	8A
Rated Voltage	300V	—	300V

2. Wire range: 26~16AWG

IEC Standard

ج

Pollution Degree	2	2	2
Overvoltage Category	II	II	II
Rate Impulse Voltage(KV)	2.5KV	2.5KV	2.5KV
Rate Voltage(V)	250V	250V	250V
Rate Current(A)	8A	8A	8A

2.wire range: 0.2-1.0mm²

NOTES2

1.Housing: PA66(UL94V-0)

2.Cover: PA66(UL94V-0)

3.C(lamp: Phosphor Brons(Sn Plated)

4.Spring: Stainless Steel

5.Button: POW

NOTES 3

1.Pitch: 3.50mm Poles: 02-24P

2.Stripping length: 10mm

3. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4. RoHS Compliance

How to order

ULO-TB01 - 15kN/3.5 - XXP - Y 0 0 0A

Certificate Series NO.	Factory Code	Customer requirements
---------------------------	-----------------	--------------------------

color:

1:Grey 2:Blue 3:Black

4:Green 5:Orange 6:Red

7:transparent 8:Yellow 9:white

ITEM	NAME OF PART	NO. OF PART	Q-TY	MATERIAL		NOTE
DWG.	Z JL	DATE	20.12.04	UNITS	MM	SHEET/OF 1/1
CHK.		DATE		SCALE	1 : 1	A4
APP.		DATE		NAME	UL0-1B01-15KN/3.5-XP0-Y000A	
				DWGNO	UL0TB01Y000A	