

NOTES:

UL Standard

1. Use group	B	C	D
Rated Current	85A	-	-
Rated Voltage	500V	-	-

2. Wire range16-4AWG

IEC Standard

1. Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(kV)	8kV
Rate Voltage(V)	750V
Rate Current(A)	101A

2. Wire range6.0-16mm²

NOTES2:

1.Housing: PA66(UL94V-2)

2.Current carrier: Steel(Zn Plated)

3.Screw: Steel(Zn Plated)

NOTES3:

1.Pitch: 16.5mm Poles: 02-12P

2.Operating temperature: -40℃~+105℃

3.RoHS Compliance

How to order

UL0-TB - PA18H - XXP - Y 0 0 0A

Certificate Factory poles Customer requirements
Series NO. Code

color:

1:Grey 2:Blue 3:Black

4:Green 5:Orange 6:Red

7:transparent 8:Yellow 9:white

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	LZW	DATE	21.04.21	UNITS	MM
CHK	DATE	SCALE	1:1	SHEET/OF	1/1
APP	DATE	NAME	UL0-TB-PA18H-XXP-Y000A		
NINGBO UL0 ELECTRONICS CO.,LTD.			DWGNO	UL0TBV000A	