

Technical data:

Product properties


- 1. Product type: Ground terminal block
- 2. Number of connections: 2
- 3. Number of rows: 1
- 4. Potentials: /

Electrical properties

- 1. Nominal voltage: /
- 2. Rated surge voltage: 8KV
- 3. Nominal current: /
- 4. Maximum load current: /
- 5. Nominal cross section: 6mm²
- 6. Overvoltage category: III
- 7. Degree of pollution: 3
- 8. Operating temperature range: -60℃~+110℃
- 9. Insulating material: PA
- 10. Flammability rating according to UL 94: V0

Connection data

- 1. Conductor cross section rigid: 0.2mm²-10mm²
- 2. Cross section AWG: 24-8
- 3. Conductor cross section flexible: 0.2mm²-6mm²
- 4. Conductor cross section, flexible AWG: 24-10
- 5. Stripping length: 10mm



Total Pitch Tolerances										Nominal dimension range										—	//
in mm										in mm										over	to
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	0	over
0	30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	200	250	320	30	all	to
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	100	to
30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	200	250	320	30	100	150	150
±0.18 ±0.20 ±0.25 ±0.3 ±0.35 ±0.4 ±0.44 ±0.55 ±0.70 ±0.75 ±0.20 ±0.25 ±0.30 ±0.35 ±0.44 ±0.55 ±0.70 ±0.80 ±0.90										0.2 0.3 0.3 0.2 0.3 0.5										0.5	
6										5										4	

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	SWL	DATE	24.1.12	UNITS	MM
CHK.	DATE	SCALE	1:1	SHEET/OF	1/1
APP.	DATE	NAME	UL0-TB140-USLKG 6N		

NINGBO ULO ELECTRONICS CO., LTD.

宁波欧路电子有限公司

DWGNO. X