

REV	E.C.N NO	CONTENT	CHK	DATE

Technical data:

Product properties



- Product type:Fuse terminal block
- Number of connections: 2
- Number of rows: 1
- Potentials: 1

Electrical properties

- Nominal voltage: 500V
- Rated surge voltage: 6KV
- Nominal current: 6.3A
- Maximum load current: 6.3A
- Nominal cross section: 4mm²
- Overvoltage category: III
- Degree of pollution: 3
- Operating temperature range: /

Connection data

- Conductor cross section rigid: 0.2mm²-6mm²
- Cross section AWG: 24-10
- Conductor cross section flexible: 0.2mm²-6mm²
- Conductor cross section, flexible AWG: 24-10
- Stripping length: 9mm-11mm



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
------	--------------	-------------	------	----------	------

DWG.	LZM	DATE	23.12.22	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	1:1	A4	
APP.		DATE		NAME	UL0-TB107-PTV4-HES1-XX		



NINGBO UL0 ELECTRONICS CO.,LTD.

宁波欧路电子有限公司

DWGNO.

ITEM	NAME OF PART	Color
------	--------------	-------

2	UL0-TB107-PTV 4 HES1 BU	Blue
1	UL0-TB107-PTV 4 HES1	Gray

Total Pitch Tolerances		Nominal dimension range																Tolerance	
		in mm																	
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	—	//
0	30	53	70	90	115	150	200	250	30	53	70	90	115	150	200	250	30	0	over
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	all	to
30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	200	250	320	100	to
±0.18	±0.20	±0.25	±0.3	±0.35	±0.4	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.4	±0.55	±0.70	±0.80	±0.90	0.2	0.3