

		2		1	
REV	E.C.N NO.	CONTENT	CHK	DATE	

Technical data:

Product properties

1. Product type: Feed-through terminal block
2. Number of connections: 2
3. Number of rows: 1
4. Potentials: 1

Electrical properties

1. Nominal voltage: 500V
2. Rated surge voltage: 6kV
3. Nominal current: 17.5A
4. Maximum load current: 17.5A
5. Nominal cross section: 1.5mm²
6. Overvoltage category: III
7. Degree of pollution: 3
8. Operating temperature range: -60℃~+110℃

Connection data

1. Conductor cross section rigid: 0.14mm^2 – 1.5mm^2
2. Cross section AWG: 26–16
3. Conductor cross section flexible: 0.14mm^2 – 1.5mm^2
4. Conductor cross section, flexible AWG: 26–16
5. Stripping length: 8mm–10mm

2	UL0-1B160-PT 15/S BU	Blue
1	UL0-1B160-PT 15/S	Gray
ITEM	NAME OF PART	Color

Total Pitch Tolerances in mm	Nominal dimension range in mm	⊥	≡	—	//
---------------------------------	----------------------------------	---	---	---	----

[illegible]

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	S.W.L	DATE	UNITS	MM	SHEET/OF 1/1
CHK.		DATE	SCALE	1 : 1	A4
APP.		DATE			
NINGBO UL0 ELECTRONICS CO.,LTD. 宁波欧路电子有限公司			NAME UL0-TB160-PT1.5/S-XX		
			DWGNO.		