

		2		1	
REV	E.C.N NO.	CONTENT	CHK	DATE	

Technical data:

Product properties

1. Product type: Multi-conductor terminal block
2. Number of connections: 3
3. Number of rows: 2
4. Potentials: 1

Electrical properties

1. Nominal voltage: 500V
2. Rated surge voltage: 6kV
3. Nominal current: 32A
4. Maximum load current: 32A
5. Nominal cross section: 4mm²
6. Overvoltage category: III
7. Degree of pollution: 3
8. Operating temperature range: /

Connection data

1. Conductor cross section rigid: $0, 2\text{mm}^2 - 4\text{mm}^2$
2. Cross section AWG: 24-12
3. Conductor cross section flexible: $0, 2\text{mm}^2 - 4\text{mm}^2$
4. Conductor cross section, flexible AWG: 24-12
5. Stripping length: 8mm



6.2

2	UL0-TB349-UK 5-TWIN BU	Blue
1	UL0-TB349-UK 5-TWIN	Gray

	Total Pitch Tolerances in mm	Nominal dimension range in mm	T	$\pm$	—	//
--	---------------------------------	----------------------------------	---	-------	---	----

[illegible]

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	YJG	DATE	24.1.12	MM	SHEET/OF 1/1
CHK.		DATE		1:1	A4
APP.		DATE			
NINGBO ULO ELECTRONICS CO.,LTD.			NAME		
宁波欧路电子有限公司			ULO-TB349-UK5-TWIN-XX		
			DWGNO.		